



FRANKOL 4T 20W-50 SG

PRODUCT DESCRIPTION:

FRANKOL 4T 20W-50 SG is a multi-grade oil for four-stroke engines of motorcycles, scooters and mopeds. It is blended by using highquality base oils and the balanced additive system of quality additive manufacturers. It has improved detergency, antiwear, anti-foam properties and offers high resistance to oxidation and corrosion.

APPLICATION:

FRANKOL 4T 20W-50 SG is intended for use in four-stroke engines of scooters, mopeds, motorcycles and ATVs, which require API SG performance level, and also for motorbikes' transmissions and clutches, which need lubrication by motor oils.

FEATURES & BENEFITS:

- Maximum engine power.
- Unsuper passed gear protection.
- Outstanding wear protection.
- Excellent shear and oxidation resistance.
- Better clutch feeling.
- Excellent low temperature fluidity

PERFORMANCE LEVELS: Meets or Exceeds:

- API SG
- JASO MA2

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			20W-50
Kinematic Viscosity@104°F/40°C	ASTM D7042	cSt	181.68
Kinematic Viscosity@212°F/100°C	ASTM D7042	cSt	19.8
Viscosity Index	ASTM D2270	-	126
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.886
FlashPoint	ASTM D92	°C	242
PourPoint	ASTM D97	°C	-24
TBN	ASTM D2896	mg KOH/g	6.0

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website Frankol.net