



FRANKOL API SN/CF FULLY SYNTHETIC

PRODUCT DESCRIPTION:

Frankol 15W-40 is an advanced performance engine oil for passenger cars and light duty commercial vehicles. This lubricant ensures optimum engine protection, keeps the engine clean and prevents sludge formation. The product meets ACEA A3/B4 requirements.

APPLICATION:

Frankol 15W-40 is recommended for passenger cars and vans with gasoline or LPG engines. It is suitable for engines with a catalyst and normally aspirated as well as turbocharged diesel engines. The product meets ACEA A3/B4 requirements.

FEATURES & BENEFITS:

- Optimal wear prevention ensuring long engine life.
- High engine cleanliness increasing engine durability.
- Premium protection against rust and corrosion.
- Stable lubricating film, even with hot oil and under excessive loads.
- High level of oxidation protection by means of selected base oils and special additives.
- Very low oil consumption.

PERFORMANCE LEVELS: Meets and Exceeds:

- API SN/CF
- ACEA A3/B4
- VW 501 01/505 00
- Fiat 9.55535-G2/D2
- MB 229.1
- RENAULT RN 0700 / 0710

TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	API SN/CF (FULLY SYNTHETIC)
Grade			15W-40
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	120
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	15.4
Viscosity Index (min)	ASTM D-2270	-	134
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm ³	0.875
Flash Point (min)	ASTM D-92	°C	236
Pour Point (max)	ASTM D-97	°C	-33
TBN	ASTM D-2896	mg KOH/g	10.2
CCS, (°C)	ASTM D-5293	m.Pa.S	<7000 (-20 °C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further Information on safety guidelines please refer to MSDS available on our website frankol.com