



FRANKOL 2T TC

SEMI SYNTHETIC / MINERAL

PRODUCT DESCRIPTION:

FRANKOL 2T is a lubricant which is designed to provide excellent performance in two stroke engines like motorcycles, scooters and mopeds. Its composition is perfectly compatible with lead-free fuels. This is a high technology product combining a perfect balance of highly refined base stocks and the latest additive's technology. It is specially formulated for use in oil injected as well as premixed gasoline/oil lubricated engines. Its increased performance provides protection against exhaust emissions and engine carbon deposits.

APPLICATION:

This oil is intended for use in two-stroke air cooled engines. Also suitable for motorcycles, scooters, mopeds, snow mobiles, lawn mowers, golf carts, chain saws and other two-stroke powered applications where API TC lubricants are recommended.

FEATURES & BENEFITS:

- Provides piston scuffing protection and reduces smoke.
- Thermal and oxidation stability.
- Specially formulated to avoid spark plug fouling.
- Perfectly adapted to unleaded fuel.
- Protection against pre-ignition problems.

PERFORMANCE LEVEL: Meets or Exceeds:

- API TC
- JASO FD
- ISO EGD

TYPICAL PROPERTIES:

| PARAMETERS | TEST METHOD | UNIT | FRANKOL 2T TC | |
|------------------------------------|-------------|-------------------|---------------|-------|
| SAE Grade | | | 20 | 30 |
| Kinematic Viscosity @ 104°F /40°C | ASTM D-7042 | cSt | 60 | 87 |
| Kinematic Viscosity @ 212°F /100°C | ASTM D-7042 | cSt | 9 | 12 |
| Viscosity Index (min) | ASTM D-2270 | - | 127 | 129 |
| SP. Gravity @15°C/ 60°F | ASTM D-4052 | g/cm ³ | 0.880 | 0.880 |
| Flash Point (min) | ASTM D-92 | °C | 130 | 130 |
| Pour Point (max) | ASTM D-97 | °C | -24 | -24 |
| TBN | ASTM D-2896 | Mg KOH/g | 2 | 2 |
| Color | ASTM D-1500 | - | Blue | Blue |

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further Information on safety guidelines please refer to MSDS available on our website frankol.com