



FRANKOL BRAKE FLUID DOT 3

PRODUCT DESCRIPTION:

FRANKOL BRAKE FLUID Dot-3 is based on polyglycol and is designed for use in hydraulic brake system of commercial vehicles, passenger cars and motorcycles operating under moderate service conditions and requiring a DOT 3 type of fluid. It provides lubrication and system protection. It also is compatible with all seals and metals used in conventional braking systems.

APPLICATION:

FRANKOL BRAKE FLUID Dot-3 is a high-performance hydraulic brake fluid for use in automotive disc, drum and anti-skid brake systems and clutch systems. Please follow OEM instructions regarding brake fluid type.

FEATURES & BENEFITS:

- Superior oxidative stability.
- High boiling point.
- Excellent low temperature fluidity ensure trouble free operation.
- Effective corrosion inhibitors provide Improved life and reliability of brake system components.

PERFORMANCE LEVELS: Meets and Exceeds:

- FMVSS 116 DOT 3
- SAE J1703
- ISO 4925 Class 3

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			DOT-3
Kinematic Viscosity@104°F/40°C	D445	cSt	>1.5
Density @20°C	D4052	g/cm ³	1.06
DRY ERBP, min	D1120	°C	> 205
WET ERBP, min	D1120	°C	> 140
pH	D1287	-	7 to 11.5

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further Information on safety guidelines please refer to MSDS available on our website frankol.com