



## FRANKOL API SF/CD MINERAL

### PRODUCT DESCRIPTION:

Frankol SAE 50 is designed to be used for passenger cars, light trucks as well as farm equipment, especially where single type of oil is preferred. This oil contains inhibitors to combat acids formation, oxidation and foaming. It is formulated with high quality mineral base stock and advance additive system.

### APPLICATION:

Gasoline and light-duty diesel engines found in passenger cars, farm and construction equipment, stationary diesel engines and four-stroke engines.

### FEATURES & BENEFITS:

- Superior viscosity retention.
- Oxidation resistant.
- Wear and friction protection.
- Engine Cleanliness and low combustion residue.
- Excellent detergency and dispersancy.

### PERFORMANCE LEVELS : Meets and Exceeds:

- API SF/ CD
- CCMC D2/G2
- MIL-L-2104D
- MB 22.71 / 228.1
- MAN 271

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	API SF/CD (MINERAL)
Grade			SAE 50
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	19.5
Viscosity Index (min)	ASTM D-2270	-	95
SP. Gravity @15°C/ 60°F	ASTM D-4052	g/cm <sup>3</sup>	TBR
Flash Point (min)	ASTM D-92	°C	220
Pour Point (max)	ASTM D-97	°C	-9

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further Information on safety guidelines please refer to MSDS available on our website frankol.com