



## FRANKOL 4T SJ SYNTHETIC / MINERAL

### PRODUCT DESCRIPTION:

FRANKOL 4T is recommended for high-performance 4T motorcycles that delivers high power efficiency and acceleration. It exceeds the fuel economy and engine cleaning requirements. It also offers excellent engine protection and superior clutch operation in all driving conditions. FRANKOL 4T is excellent in maintaining high engine power with longer drain interval.

### APPLICATION:

Recommended for all motorcycles with 4T engines. Suitable for Honda, Yamaha, Suzuki, Kawasaki, Korean and Chinese motorcycles.

### FEATURES & BENEFITS:

- Excellent shear stability.
- Provides high temperature protection.
- Outstanding wet clutch protection for maximum power transfer and smooth shifting.
- Excellent wear and corrosion protection.
- Maximizes power and acceleration.
- Added protection against harmful deposits.

**PERFORMANCE LEVEL:** Meets or Exceeds:

- API SJ
- JASO MA2

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHOD	UNIT	FRANKOL 4T SJ	
SAE Grade			10W60	20W50
Kinematic Viscosity @ 104°F /40°C	ASTM D-7042	cSt	TBR	TBR
Kinematic Viscosity @ 212°F /100°C	ASTM D-7042	cSt	24.9	19.8
Viscosity Index (min)	ASTM D-2270	-	145	120
Density@15°C/ 60°F	ASTM D-4052	g/cm <sup>3</sup>	TBR	TBR
Flash Point (min)	ASTM D-92	°C	220	220
Pour Point (max)	ASTM D-97	°C	-36	-24

### HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil into drains or the environment. Dispose to an authorized used oil collection point. For further Information on safety guidelines please refer to MSDS available on our website [frankol.com](http://frankol.com)